



















CARATTERISTICHE TECNICHE / GRES FINE PORCELLANATO COLORATO IN MASSA

TECHNICAL SPECIFICATIONS / COLOURED PORCELAIN STONEWARE
 TECHNISCHE EIGENSCHAFTEN / DURCHFÄRBTES FEINSTEINZEUG
 CARACTÉRISTIQUES TECHNIQUES / GRÈS CÉRAME FIN COLORÉ DANS LA MASSE
 CARACTERÍSTICAS TÉCNICAS / GRES FINO PORCELÁNICO COLOREADO A TODA MASA
 МЕЛНОЗЕРНИСТЫЙ КЕРАМОГРАНИТ, ОКРАШЕННЫЙ В МАССЕ
 STANDARDS : UNI EN 14411 ANNEX G - B1a / ISO 13006 ANNEX G - B1a

		SERIE ARTWORK	60x120 / 24"x47" rett. - 7 mm 60x60 / 24"x24" rett. - 7 mm	NATURALE NATURAL NATURELLE NATUR NATURAL ПРИРОДНАЯ			
CARATTERISTICHE TECNICHE TECHNICAL DATA TECHNISCHE DATEN CARACTÉRISTIQUES TECHNIQUES CARACTERÍSTICAS TÉCNICAS ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ CARATTERISTICHE DIMENSIONALI SIZE CHARACTERISTICS MASSEIGENSCHAFTEN DÉTERMINATION DES CARACTÉRISTIQUES DIMENSIONALES DIMENSIONELLES CARACTÉRISTIQUES DIMENSIONALES РАЗМЕРНЫЕ ХАРАКТЕРИСТИКИ		TIPO DI PROVA STANDARD OF TEST NORME DU TEST TEST NORM TIPO DE PRUEBA ТИП ТЕСТА		VALORI PRESCRITTI DALLE NORME INTERNATIONAL STANDARDS INTERNATIONALE NORMWERTE NORME PREVUES PAR LES NORMES VALORES PREVISTOS POR LAS NORMAS ПРЕДЪСМОТРЕННЫЕ СТАНДАРТОМ			VALORE MEDIO AVERAGE VALUE MITTELWERT VALEURS MOYEN VALOR MEDIO СРЕДНЕЕ ЗНАЧЕНИЕ
				REQUIREMENTS FOR NOMINAL SIZE N			
				7 cms/3" 15cm		Nz 15 cm	
				mm	%	mm	
 LATI SIDES SEITEN COTES CANTOS РАЗМЕРЫ СТОРОН	FOR NON-RECTIFIED TILES	EN ISO 10545-2	±0,9	±0,6	±2,0	CONFORME COMPLYING ERFÜLLT CONFORME CONFORME СОТВЕТСТВУЕТ	
	FOR RECTIFIED TILES		±0,4	±0,3	±1,0		
 SPESORE - THICKNESS DICKE - ÉPAISSEUR - ESPESOR - ТОЛЩИНА		EN ISO 10545-2	±0,5	±0,0	±0,5		
	 RETTILINEITÀ DEGLI SPIGOLI STRAIGHTNESS OF SIDES - GERADLINIGKEIT DER KANTENRECTITUDE DES ARETES - RECTITUDE DE LOS CANTOS - КОСГОФОРНОСТЬ	FOR NON-RECTIFIED TILES	EN ISO 10545-2	±0,8	±0,5	±1,5	CONFORME COMPLYING ERFÜLLT CONFORME CONFORME СОТВЕТСТВУЕТ
 ORTOGONALITÀ RECTANGULARITY RECHTWINKIGKEIT PERPENDICULARITÉ ORTOGONALIDAD КРЯВИЗНА СТОРОН	FOR NON-RECTIFIED TILES	EN ISO 10545-2	±0,8	±0,5	±2,0	CONFORME COMPLYING ERFÜLLT CONFORME CONFORME СОТВЕТСТВУЕТ	
	FOR RECTIFIED TILES		±0,4	±0,3	±1,5		
 PLANARITÀ SURFACE FLATNESS EBENLÄCHIGKEIT PLANÉTEDE DE SURFACE PLANEIDAD КРЯВИЗНА ПОВЕРХНОСТИ	CENTRE CURVATURE FOR NON-RECTIFIED TILES	EN ISO 10545-2	±0,8	±0,5	±2,0	CONFORME COMPLYING ERFÜLLT CONFORME CONFORME СОТВЕТСТВУЕТ	
	FOR RECTIFIED TILES		±0,6	±0,4	±1,8		
	EDGE CURVATURE FOR NON-RECTIFIED TILES		±0,8	±0,5	±2,0		
	FOR RECTIFIED TILES		±0,6	±0,4	±1,8		
	WARPAGE FOR RECTIFIED TILES		±0,8	±0,5	±2,0		
			±0,6	±0,4	±1,8		
 ASSORBIMENTO D'ACQUA WATER ABSORPTION WASSERANNAHME ABSORPTION D'EAU ABSORCIÓN DE AGUA ВОДОПОГЛОЩЕНИЕ		EN ISO 10545-3	≤ 0,5%			< 0,2%	
	 RESISTENZA ALLA FLESSIONE FLEXION RESISTANCE BIEGEFESTIGKEIT RESISTENCIA A LA FLEXIÓN RESISTENCIA A LA FLEXIÓN ПРЕДЕЛ ПРОЧНОСТИ ПРИ ИЗГИБЕ		EN ISO 10545-4	S ≥ 700 N Thickness < 7,5 mm			CONFORME COMPLYING ERFÜLLT CONFORME CONFORME СОТВЕТСТВУЕТ
				S ≥ 1.300 N Thickness ≥ 7,5 mm			
			R ≥ 35 N/mm ²				
 RESISTENZA ALL'URTO IMPACT RESISTANCE STOSSESTIGKEIT RESISTANCE AUX CHOCS RESISTENCIA A LOS GOLPES УДАРСТОЙКОСТЬ		EN ISO 10545-5	VALORE DICHIARATO DECLARED VALUE ANGEBENER WERT VALEUR DÉCLARÉE VALOR DECLARADO ЗАЯВЛЕННОЕ ЗНАЧЕНИЕ			> 0,80	
 COEFFICIENTE DI DILATAZIONE TERMICA LINEARE COEFFICIENT OF LINEAR THERMAL-EXPANSION LINEARER WÄRMEAUDEHNUNGSKOEFFIZIENT COEFFICIENT DE DILATION THERMIQUE LINEAIRE COEFFICIENTE DE DILATACION TERMICA LINEAL КОЭФФИЦИЕНТ ЛИНЕЙНОГО ТЕРМИЧЕСКОГО РАСТЯЖЕНИЯ		EN ISO 10545-8	VALORE DICHIARATO DECLARED VALUE ANGEBENER WERT VALEUR DÉCLARÉE VALOR DECLARADO ЗАЯВЛЕННОЕ ЗНАЧЕНИЕ			α = 6,7x10 ⁻⁶ /°C	
 RESISTENZA AGLI SBALZI TERMICI RESISTANCE TO THERMAL SHOCKS BESTÄNDIGKEIT GEGEN TEMPERATURSCHWANKUNGEN RESISTANCE AUX CHOCS THERMIQUES RESISTENCIA A LOS CHOQUES TÈRMICOS СТОЙКОСТЬ К ПЕРЕПАДАМ ТЕМПЕРАТУРЫ		EN ISO 10545-9	TEST SUPERATO SECONDO EN ISO 10545-1 TEST PASSED ACCORDING TO TEST BESTANDEN NACH TEXTE DÉPASSÉ SELON PRUEBA SUPERADA SEGUN ИСПЫТАНИЕ ПРОЙДЕНО В СООТВЕТСТВИИ С			NESSUN DANNO NO DAMAGE KEIN SCHADEN AUCUN DOMMAGE NINGUN DANO БЕЗ ПОВРЕЖДЕНИЙ	
 DILATAZIONE ALL'UMIDITÀ (IN MM/M) MOISTURE EXPANSION (IN MM/M) FEUCHTIGKEITSBEDINGTE AUSENDHUNG (IN MM/M) DILATATION À L'HYMIDITÉ (EN MM/M) DILATACIÓN CON LA HUMEDAD (EN MM/M) ВЛАЖНОСТНОЕ РАСТЯЖЕНИЕ (В MM/M)		EN ISO 10545-10	VALORE DICHIARATO DECLARED VALUE ANGEBENER WERT VALEUR DÉCLARÉE VALOR DECLARADO ЗАЯВЛЕННОЕ ЗНАЧЕНИЕ			MAX 0,1 mm / m	
 RESISTENZA AL GELO FROST RESISTANCE FROSTBESTÄNDIGKEIT RESISTANCE AU GEL RESISTENCIA AL HIELO МОРОЗОСТОЙКОСТЬ		EN ISO 10545-12	NPD			NPD	
 RESISTENZA AI PRODOTTI CHIMICI USODOMESTICO/ADDITIONI PER PISCINA RESISTANCE TO HOUSEHOLD AND SWIMMING POOL CHEMICAL PRODUCTS BESTÄNDIGKEIT GEGEN HAUSHALTSCHEMIKALIEN UND ZUSATZSTOFFE FÜR SWIMMINGPOOLS RÉISTANCE AUX PRODUITS CHIMIQUES USAGE DOMESTIQUE ET ADDITIFS POUR PISCINE RESISTENCIA A LOS PRODUCTOS QUÍMICOS DE USO DOMÉSTICO Y ADITIVOS PARA PISCINA СТОЙКОСТЬ К ДЕЙСТВИЮ ВЫСОКИХ КОНЦЕНТРАЦИЙ КИСЛОТ И ЩЕЛОЧЕЙ ДОБАВКАМ В БАССЕЙНЫ		EN ISO 10545-13	NPD			NPD	
 RESISTENZA A BASSE CONCENTRAZIONI DI ACIDI E ALCALI RESISTANCE TO LOW CONCENTRATIONS OF ACIDS AND ALKALI BESTÄNDIGKEIT BEI NIEDRIGEN KONZENTRATIONEN VON SÄUREN UND LAUGEN RÉISTANCE À BASSES CONCENTRATIONS D'ACIDES ET ALCALIS RESISTENCIA A BAJAS CONCENTRACIONES DE ÁCIDOS Y ALCALIS СТОЙКОСТЬ К ДЕЙСТВИЮ НИЗКИХ КОНЦЕНТРАЦИЙ КИСЛОТ И ЩЕЛОЧЕЙ		EN ISO 10545-13	NPD			NPD	
 RESISTENZA AD ALTE CONCENTRAZIONI DI ACIDIE ALCALI RESISTANCE TO HIGH CONCENTRATIONS OF ACIDS AND ALKALI BESTÄNDIGKEIT BEI HOHEN KONZENTRATIONEN VON SÄUREN UND LAUGEN RÉISTANCE À HAUTES CONCENTRATIONS D'ACIDES ET ALCALIS RESISTENCIA A ALTAS CONCENTRACIONES DE ÁCIDOS Y ALCALIS СТОЙКОСТЬ ДЕЙСТВИЮ ВЫСОКИХ КОНЦЕНТРАЦИЙ КИСЛОТ И ЩЕЛОЧЕЙ		EN ISO 10545-13	NPD			NPD	
 RESISTENZA ALLE MACCHIE RESISTANCE TO STAINS FLECKENBESTÄNDIGKEIT RESISTANCE AUX TACHES RESISTENCIA A LAS MANCHAS УСТОЙЧИВОСТЬ К ПЯТНООБРАЗОВАНИЮ		EN ISO 10545-14	NPD			NPD	
 CESSIONE DI PIOMBO E CADMIO LEAD AND CADMIUM DISCHARGE ABGABE VON BLEI UND CADMIUM PERTE DE PLOMB ET CADMIUM CESIÓN DE PLOMO Y CADMIO ВЫДЕЛЕНИЕ СВИНЦА И КАДМИЯ		EN ISO 10545-15	VALORE DICHIARATO DECLARED VALUE ANGEBENER WERT VALEUR DÉCLARÉE VALOR DECLARADO ЗАЯВЛЕННОЕ ЗНАЧЕНИЕ			< AL LIMITE DI RILEVAMENTO < THAN INSTRUMENT LIMIT < UNMESSBARES WERT < LIMITE DE L'INSTRUMENT < LIMITE DEL INSTRUMENTO < НА ПРЕДЕЛЕ ОПРЕДЕЛИМОСТИ	